

SEABOARD ASPHALT PRODUCTS COMPANY

AIR BARRIER - PRODUCT DATA

Product Type:	EF-400 SEABOARD MODIFIED EMULSION COATING SPRAYABLE GRADE FORMULA	
PRODUCT DESCRIPTION:	Seaboard Modified Emulsion Coating is a latex modified asphalt emulsion and is 100% ASBESTOS-FREE. This material is an asphalt emulsion with colloids and polymers to formulate an air & vapor barrier coating.	
BASIC USES:	Seaboard Modified Emulsion Coating is used as a protective coating for a variety of applications on asphalt, metal, masonry, CMU, ICF, wood, OSB and concrete surfaces.	
LIMITATIONS:	DO NOT ALLOW material to freeze. DO NOT THIN material.	
APPLICATION:	Seaboard Modified Emulsion Coating must be applied to a surface that is free from all foreign matter. This material should remain dry until it has cured. This material can be applied by brush, squeegee, or spray equipment and should yield a coverage rate of 25 square feet per gallon.	
STORAGE:	Seaboard Modified Emulsion Coating must be kept from freezing.	
COMPOSITION:	Asphalt	CAS 8052-42-4
	Water	CAS 7732-18-5
	Polymers	CAS Mixture
	Clay	CAS 14808-60-7
	Pigment Disperser	CAS Mixture

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to the suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.

SEABOARD ASPHALT PRODUCTS COMPANY

DAMPPROOFING - PRODUCT DATA

Product Type	EF-7 CLIPPERSHIP NON-FIBRED EMULSION COATING	
PRODUCT DESCRIPTION:	Clippership Non-Fibred Emulsion Coating meets ASTM-D-1227 Type II & III specifications. This material is an asphalt emulsion with selected colloids to formulate a dampproofing coating.	
BASIC USES:	Clippership Non-Fibred Emulsion Coating is used as protective coating for a variety of applications on asphalt, metal, and masonry surfaces and as an adhesive for polystyrene insulation.	
LIMITATIONS:	DO NOT ALLOW material to freeze. DO NOT THIN material.	
APPLICATION:	Clippership Non-Fibred Emulsion Coating must be applied to a surface that is free from all foreign matter. This material should remain dry until it has cured. This material can be applied by brush, squeegee, or spray equipment and should yield a coverage rate of 40 square feet per gallon.	
STORAGE:	Clippership Non-Fibred Emulsion Coating must be kept from freezing.	
COMPOSITION:	Asphalt	CAS 8052-42-4
	Water	CAS 7732-18-5
	Clay	CAS 1332-58-7

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to the suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.