Printing date 01/19/2017 Revised On 01/19/2017

#### 1 Identification of the substance and manufacturer

**IHC RED** Trade name: 80628 Product code:

PC9a Paints and coatings. **Product category** 

Manufacturer/Supplier: Kimball Midwest

4800 Roberts Road Columbus, OH 43228 800-233-1294 www.kimballmidwest.com

**Emergency telephone number:** ChemTrec: 800-424-9300

#### 2 Hazard(s) identification

#### Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

**GHS Hazard pictograms** 

GHS02 GHS04 GHS07 GHS08

Signal word Danger

**Hazard statements** Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. No smoking. **Precautionary statements** 

Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.
Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Do not breathe dust/fume/gas/mist/vapors/spray.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Protect from sunlight. Store in a well-ventilated place.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

## 3 Composition/information on ingredients

**Chemical characterization: Mixtures** 

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions

Gildinida Becompilon:		This product is a mixture of the substances listed below with hormazardous additions.			
Dangerous	Dangerous components:				
67-64-1	Acetone		18.85%		
74-98-6	propane		15.77%		
	n-butane		9.26%		
	barium sulfate, natural		8.48%		
	Isobutyl Acetate		6.48%		
2807-30-9	Glycol Ether EP		6.36%		
	n-butyl acetate		3.23%		
	PM acetate		3.21%		
	Solvent naphtha, heavy are	omatic	1.46%		
107-87-9	Methyl Propyl Ketone		1.3%		

#### 4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a

doctor.

After swallowing: Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

Dizziness effects:

Indication of any immediate medical

attention needed: No further relevant information available.

#### 5 Fire-fighting measures

**Extinguishing agents:** CO2, extinguishing powder or water spray. Fight larger fires with water spray.

(Contd. on page 2)

(Contd. of page 1)

Printing date 01/19/2017 Revised On 01/19/2017

Trade name: IHC RED

Special hazards: Protective equipment for Can form explosive gas-air mixtures.

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

firefighters:

procedures: Methods and material for containment and cleaning up: Use respiratory protective device against the effects of fumes/dust/aerosol.

Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure	controis/	personai	protection

Component				
Components with limit values that require monitoring at the workplace: 67-64-1 Acetone				
** * * * * * * * * * * * * * * * * * * *				
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm			
REL (USA)	Long-term value: 590 mg/m³, 250 ppm			
TLV (USA)	Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm			
	BEI			
74-98-6 prop	74-98-6 propane			
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm			
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm			
TLV (USA)	refer to Appendix F inTLVs&BEIs book; NIC-EX			
106-97-8 n-butane				
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm			
TLV (USA)	Short-term value: (2370) mg/m³, (1000) ppm NIC-EX			
7727-43-7 ba	arium sulfate, natural			
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction			
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction			
TLV (USA)	Long-term value: 5* mg/m³			
TEV (OOA)	*inhalable fraction; E			
110-19-0 Isobutyl Acetate				
PEL (USA)	Long-term value: 700 mg/m³, 150 ppm			
REL (USA)	Long-term value: 700 mg/m³, 150 ppm			
TLV (USA)	Short-term value: 172 mg/m³, 150 ppm			
` '	Long-term value: 238 mg/m³, 50 ppm			
123-86-4 n-b	•			
PEL (USA)	Long-term value: 710 mg/m³, 150 ppm			
REL (USA)	Short-term value: 950 mg/m³, 200 ppm			
TI \ ( (110 c)	Long-term value: 710 mg/m³, 150 ppm			
TLV (USA)	Short-term value: 712 mg/m³, 150 ppm			
Long-term value: 238 mg/m³, 50 ppm  108-65-6 PM acetate				
100-00-0 FW acetate				

WEEL (USA) Long-term value: 50 ppm

# 107-87-9 Methyl Propyl Ketone

PEL (USA)	Long-term value: 700 mg/m³, 200 ppm
REL (USA)	Long-term value: 530 mg/m³, 150 ppm
TLV (USA)	Short-term value: 529 mg/m³, 150 ppm

#### Ingredients with biological limit values:

#### 67-64-1 Acetone

BEI (USA) 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

Immediately remove all soiled and contaminated clothing. **Hygienic protection:** 

Wash hands after use.

Avoid contact with the eyes and skin. Do not eat or drink while working.

**Breathing equipment:** A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be

worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.

Nitrile gloves.

Hand protection:

Protective gloves. The glove material must be impermeable and resistant to the substance.

Printing date 01/19/2017 Revised On 01/19/2017

Trade name: IHC RED

Eye protection: (Contd. of page 2)

Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic **Odor threshold:** Not determined. pH-value: Not determined. Melting point/Melting range Undetermined. -44 °C (-47 °F) **Boiling point:** Flash point: -19 °C (-2 °F) Extremely flammable. Flammability (solid, gas): **Decomposition temperature:** Not determined.

**Auto igniting:** Product is not self-igniting.

**Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol %
Upper Explosion Limit: 10.9 Vol %
Vapor pressure: Not determined.

**Relative Density:** Between 0.77 and 0.85 (Water equals 1.00)

Vapor density

Evaporation rate
Partition coefficient: n-octonal/water: Not determined.

Solubility:
Viscosity:

Not determined.
Not determined.
Not determined.

Solids content: 31.8 %

10 Stability and reactivity

**Reactivity:** Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

#### 11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

110-19-0 Isobutyl Acetate

Oral LD50 4763 mg/kg (rbt)

123-86-4 n-butyl acetate

Oral LD50 14000 mg/kg (rat) Inhalative LC50/4 h >21.0 mg/l (rat)

108-65-6 PM acetate

Oral LD50 8500 mg/kg (rat) Inhalative LC50/4 h 35.7 mg/l (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: Irritating effect.

**Sensitization:** No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential:
Mobility in soil:
Other adverse effects:

No further relevant information available.
No further relevant information available.
No further relevant information available.

#### 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950 DOT N/A

**DOT** Consumer Commodity ORM-D

ADR Aerosols, flammable 1950 Aerosols

DR 1950 Aerosols (Contd. on page 4)

(Contd. of page 3)

# **Safety Data Sheet**

Printing date 01/19/2017 Revised On 01/19/2017

Trade name: IHC RED

Transport hazard class(es):

**Class** 2.1 Marine pollutant: No

Special precautions for user: Warning: Gases EMS Number: F-D,S-Ŭ

**Packaging Group:** 

UN "Model Regulation": UN1950, Aerosols, 2.1

### 15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulfate, natural

TSCA: All ingredients are listed.

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

108-10-1 methyl isobutyl ketone

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

California Proposition 65 chemicals known to cause birth defects or reproductive harm:

108-10-1 methyl isobutyl ketone

**CANADIAN ENVIRONMENTAL** 

All hazardous ingredients for this product appear on the Canadian Domestice Substance List. PROTECTION ACT: WHMIS Symbols for Canada:

A - Compressed gas

D2B - Toxic material causing other toxic effects



EPA:	EPA:		
67-64-1	Acetone	I	
7727-43-7	barium sulfate, natural	D, CBD(inh), NL(oral)	
110-19-0	Isobutyl Acetate	D	

# 16 Other information

Regulatory Affairs 01/19/2017 / -Contact: Date of preparation / last revision