

Class C Solutions Group

A business of MSC Industrial Supply Co.

Material Safety Data Sheet

Supply Co. - UNI-GREASE, BD1076

Document Nbr: 012018
Class C Parts IDs BD1076,BD1076-1

MATERIAL SAFETY DATA SHEET
BD1076

-----SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION -----

PRODUCT NAME: UNIGREASE BD1076
PRODUCT CODE: 1076

DISTRIBUTED BY:
CLASS C SOLUTIONS GROUP
75 MAXESS ROAD
MELVILLE, NY 11747

TELEPHONE NUMBERS AND WEBSITES:
PRODUCT INFORMATION: (866) 438-6767
REGULATORY INFORMATION: (216) 566-2902
MEDICAL EMERGENCY: (216) 566-2917
TRANSPORTATION EMERGENCY*: (800) 424-9300
*FOR CHEMICAL EMERGENCY ONLY (SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT)

-----SECTION 2 - HAZARDS IDENTIFICATION -----

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: RESPIRATORY IRRITATION, HEADACHE
,
NAUSEA, FATIGUE, DROWSINESS, IMPAIRED COORDINATION.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

SKIN: CONTACT MAY DRY THE SKIN; PROLONGED CONTACT MAY CAUSE MODERATE IRRITATION.
EYES: LIQUID OR VAPOR CAN CAUSE MODERATE TO SEVERE IRRITATION.
SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: NOT EASILY ABSORBED. SOLVENT
ACTION CAN DRY AND DEFAT THE SKIN CAUSING THE SKIN TO CRACK, LEADING TO DERMATITIS
.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: NOT A LIKELY ROUTE OF EXPOSURE. I
F

SWALLOWED, SEEK IMMEDIATE MEDICAL ADVICE AND/OR ATTENTION.

HEALTH HAZARDS (ACUTE AND CHRONIC):

ACUTE: EYE IRRITANT. POSSIBLE SKIN IRRITANT.

CHRONIC: NONE KNOWN.

CARCINOGENICITY:

NTP CARCINOGEN: NO

IARC MONOGRAPHS: NO

OSHA REGULATED: NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN.

-----SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS -----

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE MMHg @ TEMP	WEIGHT PERCENT
* HEXANE (MIXED ISOMERS), INCLUDING n-HEXANE	110-54-3	137 68	36

FOR HEXANE ISOMERS:

OSHA PEL: 500 PPM

ACGIH TLV: 500 PPM

STEL: 1000 PPM

FOR n-HEXANE:

OSHA PEL: 50 PPM

ACGIH TLV: 50 PPM

PROPANE	74-98-6	6350 68	13
---------	---------	---------	----

OSHA PEL: 1000 PPM
ACGIH TLV: ASPHYXIAANT

* INDICATES TOXIC CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III AND OF 40 CFR 372.

-----SECTION 4 - FIRST AID MEASURES -----

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION: REMOVE TO FRESH AIR. ADMINISTER OXYGEN IF NEEDED. APPLY ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. GET MEDICAL ATTENTION.

SKIN: WIPE OFF WITH TOWEL. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

EYES: WASH IMMEDIATELY WITH LARGE VOLUMES OF FRESH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

-----SECTION 5 - FIRE FIGHTING MEASURES -----

FLASH POINT: -156 DEG F

METHOD USED: ESTIMATED

FLAMMABLE LIMITS IN AIR BY VOLUME:

LOWER: 1.2

UPPER: 9.5

EXTINGUISHING MEDIA: FOAM, CO₂, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES: WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO

COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP AND EXPLOSION WHEN EXPOSED TO EXTREME

HEAT. IF WATER IS USED, FOG NOZZLES PREFERRED. WEAR GOGGLES AND SELF-CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARDS: CLOSED CONTAINERS MAY EXPLODE FROM INTERNAL PRESSURE BUILD-UP WHEN EXPOSED TO EXTREME HEAT AND DISCHARGE CONTENTS. VAPOR ACCUMULATION CAN FLASH OR EXPLODE IF IGNITED. OVEREXPOSURE TO DECOMPOSITION PRODUCTS

MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE READILY APPARENT. OBTAIN MEDICAL ATTENTION.

-----SECTION 6 - ACCIDENTAL RELEASE MEASURES -----

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: AVOID BREATHING VAPORS.

VENTILATE AREA. REMOVE ALL SOURCES OF IGNITION. CLEAN UP AREA WITH ABSORBENT MATERIAL

AND PLACE IN CLOSED CONTAINERS FOR DISPOSAL.

-----SECTION 7 - HANDLING AND STORAGE -----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE AND USE IN COOL, DRY, WELL-VENTILATED AREAS. VAPORS MAY CAUSE FLASH FIRE. KEEP AWAY FROM HEAT, SPARKS AND FLAME.

DO NOT STORE ABOVE 120 DEG F. DO NOT PUNCTURE OR INCINERATE (BURN) CANS. DO NOT STICK

PIN, NAIL OR ANY OTHER SHARP OBJECT INTO OPENING ON TOP OF CAN. DO NOT SPRAY IN EYES.

SEE PRODUCT LABEL FOR ADDITIONAL INFORMATION.

-----SECTION 8 - EXPOSURE CONTROL/PERSONAL PROTECTION -----

PRECAUTIONS: USE WITH ADEQUATE VENTILATION. TO PREVENT VAPOR BUILD-UP, OPEN DOORS AND

WINDOWS OR USE AN EXPLOSION-PROOF EXHAUST FAN TO ENSURE FRESH AIR EXCHANGE

DURING AND AFTER USE. DO NOT BREATHE VAPOR, GAS OR SPRAY MIST. WHEN USING, DO NOT EAT, DRINK OR SMOKE. AVOID CONTACT WITH EYES, SKIN AND CLOTHING. WEAR PROTECTIVE

EQUIPMENT. WASH THOROUGHLY AFTER HANDLING. REMOVE CONTAMINATED CLOTHING AND WASH IT

BEFORE REUSE. EMPTY CONTAINERS RETAIN PRODUCT RESIDUES; FOLLOW LABEL WARNINGS EVEN

AFTER CAN IS EMPTIED. DO NOT STORE IN BASEMENTS.

RESPIRATORY PROTECTION: AVOID BREATHING VAPORS. USE WITH ADEQUATE VENTILATION EQUAL TO OUT OF DOORS. IN RESTRICTED AREAS, USE APPROVED CHEMICAL/ MECHANICAL FILTERS DESIGNED TO REMOVE A COMBINATION OF PARTICLES AND VAPOR. IN CONFINED AREAS, USE APPROVED AIR LINE TYPE RESPIRATOR OR HOOD. SELF-CONTAINED BREATHING APPARATUS IS REQUIRED FOR VAPOR CONCENTRATIONS ABOVE PEL/TLV LIMITS.

VENTILATION: SUFFICIENT TO PREVENT INHALATION OF SOLVENT VAPORS. GENERAL DILUTION AND/OR LOCAL EXHAUST VENTILATION IN VOLUME OR PATTERN TO KEEP PEL/TLV OF MOST HAZARDOUS INGREDIENT BELOW ACCEPTABLE LIMIT AND LEL BELOW STATED LIMIT.

PROTECTIVE GLOVES: SOLVENT RESISTANT GLOVES REQUIRED FOR PROLONGED OR REPEATED CONTACT.

EYE PROTECTION: USE OF SAFETY GLASSES WITH SPLASH GUARDS OR FULL FACE SHIELD IS RECOMMENDED.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: USE OF SOLVENT RESISTANT APRONS OR OTHER CLOTHING IS RECOMMENDED.

WORK/HYGIENIC PRACTICES: EYE WASHES AND SAFETY SHOWERS IN THE WORKPLACE ARE RECOMMENDED.

-----SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES -----

BOILING RANGE: -44 DEG F - 149 DEG F
SPECIFIC GRAVITY (H2O=1): 0.74
VAPOR DENSITY: HEAVIER THAN AIR
EVAPORATION RATE: SLOWER THAN ETHER
SOLUBILITY IN WATER: NIL
APPEARANCE AND ODOR: AEROSOL PRODUCT

-----SECTION 10 - STABILITY AND REACTIVITY -----

STABILITY: STABLE
CONDITIONS TO AVOID: APPLICATION TO HOT SURFACES. STORAGE ABOVE 120 DEG F. EXPOSURE TO OPEN FLAME.

INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: MAY PRODUCE FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBON MONOXIDE AND OTHER TOXIC FUMES.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

-----SECTION 11 - TOXICOLOGICAL INFORMATION -----

LONG-TERM TOXICOLOGICAL STUDIES HAVE NOT BEEN CONDUCTED FOR THIS PRODUCT.

-----SECTION 12 - ECOLOGICAL INFORMATION -----

LONG-TERM ECOLOGICAL STUDIES HAVE NOT BEEN CONDUCTED FOR THIS PRODUCT.

-----SECTION 13 - DISPOSAL CONSIDERATIONS -----

WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. BEFORE ATTEMPTING CLEAN UP, REFER TO OTHER SECTIONS OF THIS MSDS FOR HAZARD CAUTION INFORMATION.

-----SECTION 14 - TRANSPORT INFORMATION -----

BY LAND: DOT PROPER SHIPPING NAME: CONSUMER COMMODITY, ORM-D
BY WATER: DOT PROPER SHIPPING NAME: UN 1950, AEROSOLS, 2.1, LTD QTY
BY AIR: DOT PROPER SHIPPING NAME: UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD QTY (PACKING INSTRUCTION Y203 APPLIES)

-----SECTION 15 - REGULATORY INFORMATION -----

ALL INGREDIENTS ARE EITHER LISTED ON THE TSCA INVENTORY OR ARE EXEMPT.

-----SECTION 16 - OTHER INFORMATION -----

DATE PRINTED: 01/07/14

NAME OF PREPARER: ESP

HMIS CODES:

H 1

F 3

R 0

P

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BECAUSE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO RESPONSIBILITY FOR ITS USE.