



## *Safety Data Sheet*

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System  
Date of Revision: 12/22/2021 Revision: 04

### Section 1 - Chemical Product and Company Identification

**1.1 Product Name: SEF 4 Cycle**

**1.2 Synonym:** Blend

**1.3** VP Racing Fuels, Inc., 7124 Richter Road, Elmendorf, TX 78112, 210.635.7744

**1.4** Recommended Use: Small Engine Fuel

**1.5** **RESTRICTIONS on USE** **THIS PRODUCT IS FOR SMALL 4 CYCLE GASOLINE ENGINE USE ONLY!**

**1.6 Emergency Response Number: CHEMTREC 800-424-9300**

**Local/International Emergency Telephone Number: +1-703-527-3887**

**1.7** See Section 16.3 for CHEMTREC in Country Emergency Number

### Section 2 - Hazards Identification

#### **2.1 GHS HAZARD**

##### Hazard Classes

##### Hazard Categories

**Flammable liquid**

**Category 1**

**Specific Target Organs toxicity single exposure**

**Category 3**

**Specific Target Organs repeated exposure**

**Category 2**

**Skin Irritation**

**Category 2**

**Acute Toxicity Oral**

**Category 4**

**Acute Toxicity Inhalation**

**Category 4**

**Mutagenicity**

**Category 1B**

**Carcinogen**

**Category 1B**

**Reproductive Toxicity**

**Category 2**

**Aspiration Hazard**

**Category 1**

**Toxic to Aquatic Life Long Lasting Effects**

**Category 2**

GHS Classification Scale (1= severe hazard; 4= slight hazard)

**2.2 Signal Word: **Danger****

## SEF 4 Cycle

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System



Flame

Health Hazard

Irritant

Aquatic Hazard

Keep away from Children

### **2.4 Hazard Statements**

#### **PHYSICAL HAZARDS:**

**224: Extremely flammable liquid and vapor.**

#### **HEALTH HAZARDS:**

**H302: Harmful if swallowed.**

**H304: May be fatal if swallowed and enter the airway.**

**H315: Causes skin irritation.**

**H332: Harmful if inhaled.**

**H336: May cause drowsiness or dizziness.**

**H340: May cause genetic defects.**

**H350: May cause cancer.**

**H361: Suspected of damaging fertility or the unborn child.**

**H373: May cause damage to organs through prolonged or repeated exposure.**

#### **ENVIRONMENTAL HAZARDS:**

**H411: Toxic to aquatic life with long-lasting effects.**

#### **PRECAUTIONARY STATEMENTS:**

**P102: Keep out of reach of children.**

**P203: Obtain special instructions before use, READ SDS BEFORE USE.**

**P210: Keep away from sparks and open flames- No smoking.**

**P233: Keep container tightly closed.**

**P240: Ground or bond container and receiving equipment.**

**P241: Use explosion-proof equipment.**

**P242 Use only non-sparking tools.**

**P243 Take precautionary measures against static discharge.**

**P260: Do not breathe mist.**

**P264: Wash hands thoroughly after handling.**

**P270: Do not eat, drink, or smoke when using this product.**

**P271: Use only outdoors or in a well-ventilated area.**

**P273: Avoid release to the environment.**

**P280: Wear protective gloves, clothing, and eye protection.**

## SEF 4 Cycle

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

### RESPONSE STATEMENTS:

P301 +P310+ P331: IF SWALLOWED: USA  
Immediately call the National POISON CENTER  
at **800-222-1222**. DO NOT induce vomiting.

P303+P361+P353: IF ON SKIN, Take off  
immediately all contaminated clothing. Rinse  
skin with water.

P304+P340: IF INHALED. Remove to fresh air  
and keep comfortable for breathing.

P305+P351: IF IN EYES: Rinse cautiously with  
water for at least 15 minutes.

P308+P313: If exposed or concerned, get  
medical attention.

P313+P332: If skin irritation persists, get  
medical attention.

H314: Get medical attention if you feel unwell.

P362+P364: IF ON CLOTHING, take off  
contaminated clothing and wash it before reuse

P370: In case of fire, use foam, carbon dioxide,  
dry chemicals to extinguish the fire.

P391: Collect spillage.

### STORAGE STATEMENTS:

P403+P235: Store in a well-ventilated place.  
Keep cool.

P405: Store locked up.

### DISPOSAL STATEMENTS:

P501: Dispose of content and container per  
local, regional, national, or international  
regulations.

**2.5 Hazards not otherwise classified (HNOC) or not covered by GHS:** Repeated exposure may  
cause skin dryness or cracking.

## Section 3 - Composition / Information on Ingredients

### 3.1

| CAS#       | EC#       | Chemical Names                                 | Percent | Classification                                                                                                                                  |
|------------|-----------|------------------------------------------------|---------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| 64741-64-6 | 265-066-7 | Naphtha<br>(petroleum), full<br>range alkylate | 45-70   | Flam. Liq. 1 H224,<br>Asp. Tox. 1 H304,<br>Skin Irrit. 2 H315,<br>STOT SE 3 H336,<br>Muta. 1B H340, Carc.<br>1B H350, Aquatic<br>Chronic 2 H411 |

## SEF 4 Cycle

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

|          |           |            |       |                                                                                                     |
|----------|-----------|------------|-------|-----------------------------------------------------------------------------------------------------|
| 78-78-4  | 201-142-8 | Isopentane | 10-30 | Flam. Liq. 1 H224, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 2 H411     |
| 108-88-3 | 203-625-9 | Toluene    | 10-30 | Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE H336, Repr. 2 H361, STOT RE 2 H373 |

**3.3 Trade Secret Provision and Chemical Concentration Disclosure:** Per OSHA and GHS Regulations, we have withheld specific percentages of the chemicals in this mixture. The chemical concentrations have been disclosed as a range and applied to the hazards as identified in this Safety Data Sheet.

### Section 4 - First Aid Measures

**4.1 Eye:** Contact with the eyes can cause irritation. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage.

**Eyes:** Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

**4.2 Skin:** Prolonged and repeated liquid contact can cause defatting and drying of the skin and lead to irritation and dermatitis.

**Skin:** Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately and wash clothing before reuse.

**4.3 Ingestion:** Liquid ingestion can cause inebriation, headache, gastrointestinal pain, nausea, and vomiting leading to central nervous system depression. Aspiration of liquid into the lungs must be avoided as even small quantities can produce chemical pneumonia, pulmonary edema, and even death.

**Ingestion:** Do NOT induce vomiting. Get medical aid immediately.

**4.4 Inhalation:** Prolonged breathing of high vapor concentrations can produce headaches, dizziness, nausea, and impaired vision. Excessive overexposure can cause central nervous system depression, loss of consciousness, liver damage, and death resulting from respiratory failure.

**Inhalation:** Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and **IF TRAINED**, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

**4.5 After first aid, get appropriate paramedic or community medical support.** The severity of outcome following exposure may be more related to the time between the exposure and treatment than the amount of the exposure. Therefore, there is a need for rapid treatment of any exposure.

## SEF 4 Cycle

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

**4.6 Note to Physicians:** If you determine that a medical emergency exists and the specific chemical identity is necessary for emergency or first-aid treatment, we will immediately disclose the specific chemical identity. Call CHEMTREC 800-424-9300 or +1-703-527-3887. We will require a written statement of need and confidentiality agreement, per OSHA's Trade Secret Regulations, as soon as circumstances permit. In non-emergency situations, we will, upon written request, disclose a specific chemical identity.

### Section 5 - Fire-Fighting Measures

**5.1 General Fire Hazards:** Use water to cool containers exposed to fire.

**5.2 Hazardous Combustion Products:** Avoid fumes of burning products.

**5.3 Extinguishing Media:** Carbon dioxide, dry chemical, foam.

**5.4 Fire Fighting Equipment/Instructions:** Firefighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

### Section 6 - Accidental Release Measures

**6.1 Spill /Leak Procedures:** Ventilate area highly flammable. Spillages of the liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition away from the spill.

**6.2 Spills:** Avoid direct contact with the material. Stop leak if without risk. Move containers from the spill area. Prevent entry into sewers or waterways. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite, or diatomaceous earth and place it in a container for disposal.

### Section 7 - Handling and Storage

**7.1 Handling Precautions:** Wash hands and exposed skin thoroughly after handling. Remove contaminated clothing and wash before reuse. Use with adequate ventilation. Avoid ingestion and contact with eyes, skin, or clothing. Keep the container tightly closed. Avoid inhalation.

**7.2 Storage Requirements:** Store in a tightly closed container in a cool, dry, and well-ventilated area.

### Section 8 - Exposure Controls / Personal Protection

#### 8.1

| Chemical Names                           | ACGIH- TLV         | OSHA - PEL         |
|------------------------------------------|--------------------|--------------------|
| Naphtha (petroleum), full-range alkylate | No TLV established | No PEL established |
| Isopentane                               | 1000 ppm TWA       | None shown         |
| Toluene                                  | 20 ppm TWA         | 200 ppm TWA        |

## SEF 4 Cycle

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

### 8.2.

**ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value.**

**OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits.**

**NOTE: TWA Means** "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour workweek which shall not be exceeded.

**8.3 Ventilation:** Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs. Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

**8.4 Contaminated Equipment:** Separate contaminated work clothes from street clothes and launder them before reuse. Remove this material from your shoes and clean personal protective equipment.

### 8.5 Personal protective equipment

#### 8.5.1 Respiratory protection

Where risk assessment shows that air-purifying respirators are appropriate, use a full-face respirator with a multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied-air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### 8.5.2 Hand protection

Handle with gloves. Gloves must be inspected before use. Use proper glove removal techniques to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Viton

Splash contact: Viton

Registered trademark of The Chemours Company FC, LLC.

#### 8.5.3 Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### 8.5.4 Skin and body protection

Impervious clothing, flame retardant antistatic protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace

### 8.6 Protective Clothing Pictograms



Splash  
Goggles



Gloves



Protective  
Apron



Vapor  
Respirator

## SEF 4 Cycle

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

### Section 9 - Physical and Chemical Properties

#### 9.1

**Physical State:** Liquid

**Appearance:** Clear

**Odor:** Aromatic Hydrocarbon Odor

**Vapor Pressure:** Not Available

**Vapor Density (Air=1):** >1

**Specific Gravity (H<sub>2</sub>O=1):** 0.7225

**Relative Density:** Not Available

**Odor Threshold:** Not Available

**Flammability (solid, gas):** Not applicable.

**Evaporation rate:** Not Available

**Partition coefficient octanol/water:** Not Available

**Water Solubility:** Insoluble

**Melting point/freezing point:** Not Available

**Flash Point:** -31.9°F (-35.5°C) close cup

**Boiling Point / Range:** 91.8-376°F  
(33.2- 191.1°C)

**Lower Explosive Limits (vol % in air):** 1%

**Upper Explosive Limits (vol % in air):** 8%

**Viscosity:** <20.5mm<sup>2</sup>/s @104°F 40°C

**Auto ignition Temperature:** Not Available

**Decomposition temperature:** Not Available

**pH:** None

### Section 10 - Stability and Reactivity

**10.1 Stability:** Stable under ordinary conditions of use and storage.

**10.2 Polymerization:** Hazardous polymerization has not been reported.

**10.3 Chemical Incompatibilities:** Strong oxidizing agents.

**10.4 Hazardous Decomposition Products:** Combustion produces carbon monoxide and carbon dioxide.

**10.5 Conditions to Avoid:** Avoid heat, sparks, open flames, and other ignition sources.

### Section 11- Toxicological Information

#### 11.1

Acute Toxicity Estimate for this blend (ATE)

ATE (Oral): 1666 mg/kg

ATE (Dermal): 2500 mg/kg

ATE (Inhalation vapor/mist): 5.9 mg/l mist

**11.1.1** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause Harmful Oral Toxicity.

**11.1.2** OECD Guideline Test results found in the European Chemical Agency Database show that no components of this product cause Harmful Dermal Toxicity.

**11.1.3** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause Harmful Inhalation Toxicity.

**11.2 Route of Entry:** Inhalation, Ingestion, Absorption, Skin, and Eye Contact.

**11.3 Aspiration Hazard:** European Chemical Agency Database shows that components of this product may be fatal if swallowed and enters airways.

**11.4 Mutagenicity:** OECD Guideline Test results found in the European Chemical Agency Database show components of this product to cause genetic defects.

## SEF 4 Cycle

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

**11.5 Skin Corrosion/Irritation:** OECD Guideline Test results found in the European Chemical Agency Database shows that no components of this product cause skin irritation. Repeated exposure may cause skin dryness or cracking.

**11.6 Serious Eye Damage/Irritation:** OECD Guideline Test results found in the European Chemical Agency Database shows that no components of this product cause serious eye irritation. However can irritate eyes.

**11.7 Reproductive toxicity:** OECD Guideline Test results found in the European Chemical Agency Database show components of this product to cause damage to fertility or the unborn child.

**11.8 Skin Sensitization** OECD Guideline Tests results found in the European Chemical Agency Database show no components of this product to cause skin sensitivity.

**11.9 Respiratory Sensitization** OECD Guideline Tests results found in the European Chemical Agency Database show no components of this product to cause respiratory sensitivity.

**11.10 Specific Target Organ Toxicity (Single Exposure):** European Chemical Agency Database shows that components of this product may cause damage to the central nervous system (CNS).

**11.11 Specific Target Organ Toxicity (Repeated Exposure):** Contains chemicals that may cause damage to the following organs: kidneys, lungs, liver, upper respiratory tract, skin, eyes, central nervous system (CNS).

**11.12 Signs and Symptoms:** Effects due to exposure may include: Headache, Dizziness, Drowsiness, Metabolic Acidosis, Coma, Seizures. Symptoms may be delayed.

**11.13 Carcinogenicity:** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause cancer.

## Section 12 - Ecological Information

### 12.1

| Product Name                             | Results        | Species | Exposure |
|------------------------------------------|----------------|---------|----------|
| Naphtha (petroleum), full range alkylate | LC50 3.1 mg/l  | Fish    | 96 hours |
| Naphtha (petroleum), full range alkylate | EL50 4.5 mg/l  | Daphnia | 48 hours |
| Naphtha (petroleum), full range alkylate | EL50 45 mg/l   | Algae   | 96 hours |
| Isopentane                               | LC50 34.5 mg/l | Fish    | 96 hours |
| Isopentane                               | EC50 59.4 mg/l | Daphnia | 48 hours |
| Isopentane                               | EC50 10.7 mg/l | Algae   | 96 hours |
| Toluene                                  | LC50 7.63 mg/l | Fish    | 96 hours |
| Toluene                                  | EC50 6 mg/l    | Daphnia | 48 hours |

**Toxicity:** OECD Guideline Test results found in the European Chemical Agency Database show this product's components to cause long-term toxicity to aquatic life.

**12.2 Mobility:** Floats on water.

**12.3 Persistence/degradability:** Inconclusive technical data.

## SEF 4 Cycle

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

**12.4 Bioaccumulation:** Inconclusive technical data.

**12.5 Other adverse effects:** Inconclusive technical data.

### Section 13 - Disposal Considerations

**13.1 Disposal: DO NOT REUSE EMPTY CONTAINER!** The container should be emptied before discard. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

### Section 14 - Transport Information

#### 14.1 DOT Transport Information



**ID No.:** UN 1203

**Shipping Name:** Gasoline

**Hazard Class:** 3

**Packing Group:** II

**Label:** Flammable

**Placard:** Flammable

**Marking:** MARINE POLLUTANT Alkylate Full Range when shipping ground greater than 119 gallons' s  
ingle container or any quantity by water

**Special Provision:** 177 Gasoline, or ethanol and gasoline mixtures, for use in internal combustion engines (e.g., in automobiles, stationary engines, and other engines) must be assigned to Packing Group II regardless of variations in volatility.

#### 14.2 IMDG Transport Information



**ID No.:** UN 1203

**Shipping Name:** GASOLINE

**Hazard Class:** 3

**Packing Group:** II

**Flash Point:** (-35.5°C c.c.)

**EmS Number:** F-E, S-E

**Label:** Flammable

**Placard:** Flammable


**Marking:** Marine Pollutant Naphtha (petroleum), full-range alkylate

**Special Provision:** 243 Gasoline, motor spirit, and petrol, for use in internal combustion engines (e.g., in automobiles, stationary engines, and other engines) shall be assigned to entry regardless of variations in volatility.

## SEF 4 Cycle

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

### 14.3 UN Dangerous Goods Transport Information



**ID No.:** ID No.: UN1203

**Shipping Name:** Gasoline

**Hazard Class:** 3


**Packing Group:** II

**Label:** Flammable

**Placard:** Flammable

**Marking:** Marine Pollutant Naphtha (petroleum), full-range alkylate

**Special Provision:** 243 Gasoline, motor spirit, and petrol, for use in internal combustion engines (e.g., in automobiles, stationary engines, and other engines) shall be assigned to entry regardless of variations in volatility.




### 14.4 DOT Transport Limited Quantity/Consumer Commodity

Inner packaging not over

1.0L (0.3 gallons) net capacity each.

Outer Package not over 30kg (66lbs) each



### 14.5 IMDG Transport Limited Quantity

Inner packaging not over

1.0L (0.3 gallons) net capacity each.

Outer Package not over 30kg (66lbs) each

**ID No.:** UN 1203

**Shipping Name:** GASOLINE LTD.QTY.

**Hazard Class:** 3

**Packing Group:** II

**Flash Point:** (-35.5° C c.c.)

**EmS Number:** F-E, S-E

**NOTE:** Because the MARINE POLLUTANT Naphtha (petroleum), full-range alkylate in the inner packaging of the combination packaging is a net quantity of 5 L or less. The MARINE POLLUTANT marking is not required.

**Special Provision:** 243 Gasoline, motor spirit, and petrol, for use in internal combustion engines (e.g., in automobiles, stationary engines, and other engines) shall be assigned to entry regardless of variations in volatility.

## SEF 4 Cycle

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

### Section 15 - Regulatory Information

#### 15.1 US Regulations

**US. Toxic Substances Control Act:** All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

**Toxic Release Inventory (TRI):** This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know- Act of 1986 (40 CFR 372):

| CAS Number | Chemical Name | Chemical percentage by weight not exceeding |
|------------|---------------|---------------------------------------------|
| 108-88-3   | Toluene       | 20%                                         |
| 110-54-3   | n-Hexane      | At demines% limits                          |
| 100-41-4   | Ethylbenzene  | At demines% limits                          |

This information must be included in all SDSs copied and distributed for this material.

**CERCLA Hazardous Substances and corresponding RQs:** Toluene 1000lbs. n-Hexane 5000 lbs. Ethylbenzene 1000 lbs.

**SARA Community Right-to-Know Program:** All components of this blend.

**Clean Water Act:** None.

**OSHA:** All ingredients are regulated by 29 CFR 1910.1200.

#### State Regulations

#### State Regulations

#### California prop. 65



**WARNING** This product can expose you to chemicals including Ethylbenzene CAS # 100-41-4 and Toluene CAS # 188-88-3, and n-Hexane CAS # 110-54-3, which are known to the State of California to cause cancer and birth defects, or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemicals on the following State Right to Know Lists:

**Massachusetts:** All components of this product are on the Massachusetts Inventory or are exempt from Inventory requirements.

**New Jersey** All components of this product are on the New Jersey inventory or are exempt from Inventory requirements.

**Pennsylvania:** All components of this product are on the Pennsylvania Inventory or are exempt from Inventory requirements.

### Section 16 - Other Information

**16.1 Disclaimer:** The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall determine the product's suitability for their particular purpose and that they assume the risk of their use.

## SEF 4 Cycle

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

**16.2 References:** CHEMpendium database of the Canadian Centre for Occupational Health and Safety (CCOHS), European Chemical Agency Data Base, and MSDS and SDS of chemicals in this mixture.

**16.3 CHEMTREC in-country emergency dial numbers:**

| County              | Greeting Language      | City             | Local number     | Toll-Free number |
|---------------------|------------------------|------------------|------------------|------------------|
| Argentina           | Latin American Spanish | Buenos Aires     | 54-1159839431    |                  |
| Brazil              | Portuguese             | Rio De Janeiro   | 55-2139581449    |                  |
| Brazil              | Portuguese             | Sao Paulo        | 55-1143491359    |                  |
| Brazil - Toll-Free  | Portuguese             |                  | 0800 892 0479    | 0800 892 0479    |
| Cayman Islands      | English                | Local (National) | 345-749-8392     |                  |
| Chile               | Latin American Spanish | Santiago         | 56 2 2581 4934   |                  |
| Colombia            | Latin American Spanish |                  | 01800-710-2151   | 01800-710-2151   |
| Costa Rica          | Latin American Spanish |                  | 506-40003869     |                  |
| Dominican Republic  | Latin American Spanish | Santo Domingo    | 1 (829) 956-7588 |                  |
| El Salvador         | Latin American Spanish | San Salvador     | 503 2136 7633    |                  |
| Grenada             | English                | St George        | 1 (473) 230-0165 |                  |
| Guinea              | French                 |                  | 224 660 71 03 00 |                  |
| Mexico              | Latin American Spanish |                  | 01-800-681-9531  | 01-800-681-9531  |
| Panama              | Latin American Spanish |                  | 507-8322475      |                  |
| Peru                | Latin American Spanish | Lima             | 51-17071295      |                  |
| Trinidad and Tobago | English                | National Number  | 1-868-224-5716   |                  |

|       |                         |  |                  |                  |
|-------|-------------------------|--|------------------|------------------|
| India | Hindi, Bengali, English |  | 000-800-100-7141 | 000-800-100-7141 |
|-------|-------------------------|--|------------------|------------------|

## SEF 4 Cycle

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

|              |                            |              |                                         |                                   |
|--------------|----------------------------|--------------|-----------------------------------------|-----------------------------------|
| Indonesia    | Indonesian                 |              | 001-803-017-9114                        | 001-803-017-9114                  |
| Israel       | Hebrew                     | Tel Aviv     | 972-37630639                            |                                   |
| Japan        | Japanese                   | Tokyo        | 81-345209637                            |                                   |
| Malaysia     | Malay                      | Kuala Lumpur | 60-392125794                            | 1-800-815-308                     |
| Philippines  | Tagalog                    | Manila       | +63 2 8395 3308 and<br>1-800-1-116-1020 | 1-800-1-116-1020                  |
| Russia       | Russian                    |              | 8-800-100-6346                          | 8-800-100-6346                    |
| Saudi Arabia | Arabic and English         |              | 966-8111095861                          |                                   |
| Singapore    | English and<br>Mandarin    |              | 65-31581349                             | 800-101-2201                      |
| South Korea  | Korean                     |              |                                         | 003-0813-2549<br>and 080-822-1374 |
| Taiwan       | Mandarin                   | Taipei       | 886-2-7741-4207                         | 00801-14-8954                     |
| Thailand     | Thai                       |              | 001-800-13-203-<br>9987                 | 001-800-13-203-<br>9987           |
| India        | Hindi, Bengali,<br>English |              | 000-800-100-7141                        | 000-800-100-7141                  |

|             |         |          |              |  |
|-------------|---------|----------|--------------|--|
| Australia   | English | Sydney   | 61-290372994 |  |
| New Zealand | English | Auckland | 64-98010034  |  |

|              |         |      |               |               |
|--------------|---------|------|---------------|---------------|
| South Africa | English | None | 0-800—983-611 | 0-800—983-611 |
|--------------|---------|------|---------------|---------------|

### 16.4 SDS Preparation Date 01/24/2016

**SDS Previous Issue Date:** None

**SDS Revision Date:** 01/24/2019 Sections 2,3,8,11,12,14,15,16

**SDS Revision Date:** 04/03/2020 Sections 2,8,9,11,13,15,16

**SDS Revision Date:** 12/22/2021 Sections 2,3,8,11,12,14,15,16

Prepared by SJC Compliance Education, Inc

1319 Varese Dr.

Pearland, TX. 77581

[steve@sjcedu.org](mailto:steve@sjcedu.org)

END OF SAFETY DATA SHEET