

MATERIAL SAFETY DATA SHEET

Page 1 of 3



PRESS-SEAL GASKET CORPORATION

800-348-7325 - (219) 436-0521
P.O. BOX 10482 FORT WAYNE, INDIANA 46852
6935 LINCOLN PARKWAY FORT WAYNE, INDIANA 46804

ADHESIVE #1-326

Section One

PRODUCT INFORMATION

MANUFACTURER'S NAME: Pemco Adhesives. Business Phone No: 1-219 295-8384
MANUFACTURER'S ADDRESS: 5120 Beck Drive Emergency Phone No.: 1-800-424 9300
Elkhart, Indiana 46516 Date prepared 02-Jan-97

PRODUCT NAME: Pemco 126
PROPER SHIPPING NAME: #1-326 Adhesive

Section Two

HAZARDOUS INGREDIENTS INFORMATION

CHEMICAL NAME	C.A.S. No.	% BY WEIGHT	ACGIH TLV	OSHA PEL
Rubber Solvent Naptha		65	400 ppm	64742-89-8
Toluol		<5	100 ppm	108-88-3

Section Three

PHYSICAL AND CHEMICAL DATA

PHYSICAL STATE: SOLID ☐ LIQUID ☒ PASTE ☐
APPEARANCE & ODOR: Red liquid with hydrocarbon odor
BOILING POINT: 114 F°
SPECIFIC GRAVITY (water = 1): 1.0
EVAPORATION RATE (ethyl ether = 1): N.A.
SOLUBILITY IN WATER: Negligable
VAPOR PRESSURE: N.A.
VAPOR DENSITY (air = 1): >1
PERCENT SOLIDS (by weight):
MELTING POINT: N.A.

Section Four

FIRE & EXPLOSION HAZARD DATA

FLASH POINT: < 0° F (TCC) Method Used: NA
FLAMMABLE LIMITS: LEL: 1.2% UEL: 7.4%
AUTO-IGNITION TEMPERATURE: N/A
PROPER EXTINGUISHING MEDIA: Foam, dry chemical or carbon dioxide. Water may be ineffective, but water should be used to keep fire exposed containers cool.
RECOMMENDED FIREFIGHTING PROCEDURES: SCBA; Turn out gear
FIRE AND EXPLOSION HAZARDS: Keep work area free from hot metal surfaces and other sources of ignition

ADHESIVE #1-326**Section Five****REACTIVITY DATA**

STABILITY: Stable

CONDITIONS TO AVOID: Avoid strong oxidizing agents, strong acids or bases and selected amines.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition in the presence of air yield carbon monoxide

HAZARDOUS POLYMERIZATION: Will Not Occur

Section Six**HEALTH HAZARD DATA**

SIGNS AND SYMPTOMS OF EXPOSURE: High Vapor concentrations are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anesthetic and may have other central system effects.

ACUTE: Dizziness, headaches to unconsciousness

CHRONIC: Drying and defating of the skin.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None Known.

IS CHEMICAL LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN:

NATIONAL TOXICOLOGY PROGRAM : No

I.A.R.C. MONOGRAPHS: No

OSHA: No

EMERGENCY AND FIRST AID PROCEDURES:

IN EYES: Flush with large amounts of water, frequently flushing under the lids. Get medical attention.

ON SKIN: Wash with soap and water, Remove contaminated clothing.
Get medical attention of irritation persists.

INHALED: Remove effected person to fresh air, Give oxygen or artificial respiration as necessary to assist breathing, Get medical attention.

INGESTED: Do not induce vomiting, Get medical attention.

EMERGENCY AND FIRST AID PROCEDURES: If overcome by vapors from solvents, move to fresh air.

Section Seven**PRECAUTIONS and SPILL/LEAK PROCEDURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Small Spill: Absorb liquid sawdust or floor absorbent. Transfer to a container

Large Spill: Eliminate all ignition sources; use absorbant; transfer to a container.

WASTE DISPOSAL METHOD: If this product becomes a waste, it is considered a hazardous waste due to its ignitability. Dispose of in accordance with local, state, and federal environmental and waste regulations.

STORAGE AND HANDLING PROCEDURES: Keep containers closed when not in use. Keep away from heat. Do not store or handle near an ignition source, or flames. Keep containers closed when not in use and in a cool area.

ADHESIVE #1-326

Section Eight

SPECIAL PROTECTION INFORMATION CONTROL MEASURES

RESPIRATORY PROTECTION: Use NIOSH approved cartridge respirator
VENTILATION: Face velocity > 60 fpm; Explosion proof ventilation equipments
EYE PROTECTION: Use safety goggles.

HAND PROTECTION: Not normally needed.

WORK/ HYGIENE PRACTICES: Keep containers closed when not in use. Use in well ventilated area. Wash hands after using product.

DATE OF PREPARATION: January 7, 1997

THIS INFORMATION RELATES TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF OUR KNOWLEDGE AND BELIEF ACCURATE AND RELIABLE AS OF THE DATE COMPILED. HOWEVER, NO REPRESENTATION, WARRANTY, OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY, OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE. WE DO NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE THAT MAY OCCUR FROM THE USE OF THIS INFORMATION NOR DO WE OFFER WARRANTY AGAINST PATENT INFRINGEMENT.