ConSeal[™] CS-50

Solvent Based Liquid Butyl Primer





Surface Preparation Coating and Installation Aid for Concrete and Metal Surfaces

Applications

For use on concrete or metal surfaces, CS-50 Solvent Based Surface Primer is a concrete surface preparation coating and installation aid for bonding preformed sealants. CS-50 Solvent Based Surface Primer can be applied in advance of product installation.

Sealing Properties

When applied to concrete or metal, ConSeal CS-50 Liquid Butyl Primer creates a butyl rubber film that acts to both seal the structure and improve the bond of preformed sealants.

Physical Properties

Description

Color: Black

% Solids: 20% minimum Solvent Type: VMP Naptha

Flash Point: 76°F

Weight / Gallon:

Dry Time @ 77°F (25°C):

Dry Time @ 40°F (4°C):

Clean Up:

7.6 Pounds

15-20 minutes

30-40 minutes

Mineral Spirits

Coverage Per Gallon: Approx. 300 sq ft on wet cast concrete.

Min. Storage Temperature: 32°F
Min. Application Temperature: 0°F

Surface When Dry: Flat Black, non-tacky

Shelf Life: 6 months

Limited Warranty

This information is presented in good faith, but we cannot anticipate all conditions under which this information and our products, or the products of other manufactures in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products, either alone or in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each such product or product combinations for their own purposes. It is the users' responsibility to satisfy himself as to the suitability and completeness of such information for this own particular use. We sell this product without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of this product, whether used alone or in combination with other products.

Don't Just Seal It, ConSeal It!

© 2018 Concrete Sealants, Inc.

